



# Flexible Installation & Increased Air Circulation

## INDOOR FEATURES

- Available in 208/230V
- Up to 22.5 SEER and up to 12.0 HSPF when paired with DLCSRA outdoor unit
- Modes: Cool, Heat, Dry, Fan, Auto
- Vertical or horizontal installation
- Up to 0.64 in WG
- Rear or bottom return
- Constant CFM operation
- Built-in condensate lift pump
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation, as low as 30 dB(A)
- Aluminum Golden Hydrophilic pre-coated fins

## COMPATIBLE WITH:

- DLCSRA Outdoor Unit Single Zone (p 19)
- DLCMRA Outdoor Unit Multi-Zone (p 45)

Sizes: 09 / 12 / 18 / 24

Select sizes are ENERGY STAR® certified based on outdoor unit pairing



## KEY FEATURES

### Vertical or Horizontal Installation

Designed for maximum installation flexibility with the built-in secondary drain pan, which allows the unit to be mounted vertically for either a floor- or ceiling-concealed installation depending on existing conditions.

### Built-In Condensate Lift Pump

Supplied with a condensate lift pump that is capable of lifting the water 29.5 in. (750 mm.) above the top of the unit.

## CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller KSACN0101AAA (Timer Function)

Wired Remote Controller KSACN0501AAA (7-Day Programmable) included with indoor unit



Wired Controller (Timer Function) KSACN0101AAA



Wired Controller (7-Day Programmable) KSACN0501AAA



Wireless Remote Controller

## ACCESSORIES

Wi-Fi® Kit KSAIF0401AAA





**SPECIFICATIONS:**

DLFSDA Ducted Heat Pump System					
Size		9	12	18	24
Indoor Model		DLFSDAH09XAK	DLFSDAH12XAK	DLFSDAH18XAK	DLFSDAH24XAK
Electrical					
Voltage-Phase-Cycle		V-Ph-Hz	208/230-1-60	208/230-1-60	208/230-1-60
Power Supply		Indoor unit powered from outdoor unit			
MCA		A.	1.11	1.11	1.2
Operating Range					
Cooling Indoor DB Min - Max		° F (° C)	62~90 (17~32)	62~90 (17~32)	62~90 (17~32)
Heating Indoor DB Min - Max		° F (° C)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)
Piping					
Pipe Connection Size - Liquid		in (mm)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)
Pipe Connection Size - Suction		in (mm)	3/8 (9.52)	1/2 (12.7)	1/2 (12.7)
Indoor					
Unit Width		in (mm)	27.56 (700)	27.56 (700)	34.65 (880)
Unit Height		in (mm)	7.87 (200)	7.87 (200)	8.27 (210)
Unit Depth		in (mm)	19.92 (506)	19.92 (506)	26.54 (674)
Net Weight		lbs (kg)	43.56 (19.8)	43.56 (19.8)	54 (24.5)
Number of Fan Speeds			3	3	3
Airflow (lowest to highest)		CFM	147/211/264	176/282/353	300/400/480
Sound Pressure (lowest to highest)		dB(A)	30/34/38	35/37/39	35/37/39
Max. Static Pressure		in (WG)	0.20	0.20	0.40
Field Drain Pipe Size O.D.		in (mm)	1 (25.4)	1 (25.4)	1 (25.4)

**COMPATIBILITY:**

Indoor Unit	DLFSDAH09XAK	DLFSDAH12XAK	DLFSDAH18XAK	DLFSDAH24XAK
Outdoor Unit Single Zone*	DLCSRAH09AAK	DLCSRAH12AAK	DLCSRAH18AAK	DLCSRAH24AAK
Outdoor Unit Multi-Zone*	DLCMRAH18BAK			
	DLCMRAH27CAK			
			DLCMRAH36DAK	
			DLCMRAH48EAK	

\*Performance may vary based on the compatible outdoor units. See respective pages for performance data.