PRO PRO1 SUBMITTAL SHEET

Job Name:	Location:	Date:
Purchaser:		_ Installer:
Submitted to:		For: RNC R&R Commercial

MODEL T751i

Universal - WIFI 2 Heat, 2 Cool Conventional 4 Heat, 2 Cool Heat Pump Hardwire Only Programmable Through App

This model features:

- 7 sq. inch display
- Blue backlight
- Glow in the dark light button
- Universal subbase
- Simple private label badge system
- Setpoint limits
- 24V power

Specifications:

Application Programmability Changeover **Display Range Control Range** Display Accuracy Heat Swing Cool Swing Terminals Load Rating **Power Source Operating Ambient Operating Humidity** Mounting **Dimensions** Warranty

2 Heat, 2 Cool Conventional / 4 Heat, 2 Cool Heat Pump Programmable Through App System Switch 41°F to 95°F (5°C to 35°C) 44°F to 90°F (7°C to 32°C) +/- 1°F Adjustable from 0.2°F to 2.0°F Adjustable from 0.2°F to 2.0°F Rc, Rh, Y, Y2, W2, W/E, G, B, O 1 amp per terminal, 1.5 amp maximum all terminals combined 18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) 32°F to +105°F (0°C to +41°C) 90% non-condensing maximum Wall or Junction Box 4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D) 5 year warranty







- 5 Year warranty
- 5 minute compressor delay protection (selectable on or off)
- Customizable staging logic
- Separate heating and cooling swing (cycle rate) adjustments
- Auto Changeover